ABS Sheets with High Quality Wood Grain Laminate









ABS Wood Grain

ABS Sheets with High Quality Wood Grain Laminate

Advantages

Ideally suited for vacuum forming and precision CNC machining Available in a wide range of wood grains and colors Combination of excellent elasticity and high impact resistance

Applications

Ideal for automotive fixtures, household products, furniture, advertising and display stands

Max. Dimensions

Width: 1,250 mm Length: 3,000 mm

Thickness: 1.0 mm - 5.0 mm Specific Gravity: 1.05 gr/ccm

Physical Properties			ISO	ASTM	DIN	Value
Density	kg/m³		1183B	D-792-B	53479-B	1050
Thermal Properties						
Vicat softening point (12	٠.	°C	306A	D-1525-B	53460	110
HDT, annealed (120°C/h	, 1.80MPa)	°C	75/A	D-648	53461-A	101
Mechanical Propertie	es					
Tensile at yield, 100 mm.	/min.	MPa	DIS527/D	D-638-M	53455-6-3	42
Elongation at break		%	DIS527/D	D-638	53455-6-3	4.0
Flexural strength, 1 mm/min.		MPa	178	D-790-M	53452	65
Flexural modulus, 3 point		MPa	178	D-790-M-A	53457-B3	2050
Izod notched 23°C		KJ/m ²	180/1A			28
Charpy notched 23°C		KJ/m ²	179/2C	53453		15
Rockwell hardness, R-scale			2039/2	D-785B		80
Flammability Ratings	5					
Flame class rating (1)			all colours			НВ

- Typical properties, not to be construed as specification limits
- (1) This numerical flame-spread rating is not intended to reflect hazards by material under actual fire conditions

